

XR2000 ACTIVE MONITORING HARDWARE ENDPOINT FOR THE HAWKEYE™ AND IXCHARIOT® PRODUCT LINES

NETWORK AND APPLICATION PERFORMANCE ASSESSMENT AND MONITORING DEMARCATION HARDWARE

A new-generation appliance, Ixia's XR2000 Active Monitoring Endpoint provides extensive network and application performance assessment and monitoring demarcation. The hardware endpoint features easy setup and management for seamless integration into live network environments.

The XR2000 endpoint works with Ixia's Hawkeye and IxChariot, allowing assessment and monitoring of network and application performance in only two clicks.

KEY FEATURES

- Field ready: robust and fan-less, lightweight
- Secured access with embedded firewall
- VGA output and console-ports output for easy management
- Automatic boot
- Web-based configuration
- Advanced routing support (VLAN, source based routing)
- Up to line-rate generation
- Active traffic generation supporting 150+ applications
- Endpoint-to-endpoint tests: UDP, TCP traffic, voice, video, traffic mixes
- One-arm testing against web servers (HTTP/HTTPS), DNS, and cloud services (YouTube, Dropbox)
- Remote management and configuration from Hawkeye
- IxChariot 9 registration server easy configuration
- In-band or out-of-band management support

HIGHLIGHTS

- Next-generation active endpoint appliance
- Robust, portable, field-ready
- Secured access with embedded firewall
- Web-based configuration
- Advanced routing support
- Active traffic generation supporting 150+ applications
- Up to line-rate generation
- Endpoint-to-endpoint tests: UDP, TCP traffic, voice, video, and traffic mixes
- Remote management and configuration from Hawkeye
- Online upgrades
- In-band or out-of-band management supported



SPECIFICATIONS

CPU Type	Intel Atom D525 1.8 Hz (dual core processor)
DRAM	2G
Storage	8G flash
I/O Interfaces	2 USB, 1 VGA, 1 COM
LAN	6 x 10 / 100 / 1000 Mbps
Power	On-board DC +12V \pm 5% converts to +3.3V/+5V/+12V for system – max 60W
Dimension	200mm x 42mm x 144mm - 7.9" x 1.65" x 5.67" – 1U
Weight	1.2 Kg
Operation Temperature	0 ~ 40 °C - Storage: -20°C~70°C
Operation Humidity	5 ~ 95%, non-condensing

SUPPORTED PROTOCOLS

Protocols for Node-to-Node or One-Arm Tests	TCP, UDP, RTP, HTTP, HTTPS, FTP, NTP, DNS, POP,SMTP, ICMP, IGMPv2, IGMPv3, RTSP, RADIUS, DHCP, PPPOE
--	--

PERFORMANCE

TCP Throughput	Up to line rate (1G)
UDP Throughput	Up to line rate (1G)
Voice Calls	Up to 300 simultaneous calls
Streaming Traffic (Lync, Unified Communications)	Up to 200 simultaneous mixed voice/video calls
Streaming Traffic (Video)	Up to 700Mbps of video traffic

ORDERING INFORMATION

940-0008

XR2000 Active Hardware Endpoint; integrated hardware endpoint for Hawkeye or IxChariot; Licensed for 2 active test ports; AC unit.

IXIA WORLDWIDE HEADQUARTERS

26601 AGOURA RD.
CALABASAS, CA 91302

(TOLL FREE NORTH AMERICA)

1.877.367.4942

(OUTSIDE NORTH AMERICA)

+1.818.871.1800

(FAX) 818.871.1805

www.ixiacom.com

IXIA EUROPEAN HEADQUARTERS

IXIA TECHNOLOGIES EUROPE LTD
CLARION HOUSE, NORREYS DRIVE
MAIDENHEAD SL6 4FL
UNITED KINGDOM

SALES +44.1628.408750

(FAX) +44.1628.639916

IXIA ASIA PACIFIC HEADQUARTERS

101 THOMSON ROAD,
#29-04/05 UNITED SQUARE,
SINGAPORE 307591

SALES +65.6332.0125

(FAX) +65.6332.0127